

Project #:_		
Item #:		



Model RCS10DSE shown

Medium Volume This category of microwave is ideal for...

Applications:

- Coffee shops
- Ethnic restaurants
- Concessions
- Dessert stations

All ACP, Inc. commercial ovens are backed by our Culinary Center. Call us with any question regarding food preparation, menu development and cooking times. 866-426-2621.



Medium Volume

Amana Commercial Microwave Model RCS10DSE

Power Output

- 1000 watts of power.
- Four power levels.

Easy to Use

- User friendly ten minute dial timer lights up for at-a-glance monitoring.
- Timer automatically resets to zero if door is opened during heating. User option allows manual reset to zero.
- See-through door and lighted interior for monitoring without opening the door.
- 1.2 cubic ft. (34 liter) capacity accommodates a 14" (356 mm) platter, prepackaged foods and single servings.
- Stackable to save valuable counter space.

Easy to Maintain


- Stainless steel exterior and interior for easy cleaning and a commercial look.
- Constructed to withstand the foodservice environment.
- Non-removable air filter protects oven components.
- Backed by the ACP, Inc. 24/7 ComServ Support Center, 866-426-2621.
- ETL Listed.







Amana Commercial Microwave Model RCS10DSE | Medium Volume



Installation clearance: 2" all sides

Drawings available from KCL CADlog - techs@kclcad.com

Connai Continua	П
Specifications Model	RCS10DSE UPC Code 728028129465
Configuration	Countertop
Control System	Dial
Max. Cooking Time	10:00
Power Levels	4
Time Entry Option	Yes
Microwave Distribution	Rotating antenna, top
Magnetron	1
Stackable	Yes
Stage Cooking	1
Interior Light	Yes
Door Handle	Grab & Go
Signal	End of cycle
Exterior Dimensions	H 13 ¾" (352) W 22" (559) D*19" (483)
Cavity Dimensions	H 8 ½" (216) W 14 ½" (368) D 15" (381)
Door Depth	32 ¾" (832), 90°+ door open
Usable Cavity Space	1.2 cubic ft. (34 liter)
Exterior Finish	Stainless steel
Interior Finish	Stainless steel
Power Consumption	1550 W, 13 A
Power Output**	1000 W** Microwave
Power Source	120V, 60 Hz, 15 A single phase
Plug Configuration / Cord	NEMA 5-15 5 ft. (1.5m)
Frequency	2450 MHz
Product Weight	41 lbs. (18.6 kg.)
Ship weight (approx.)	47 lbs. (21.3 kg.)
Shipping Carton Size	H 17" (432) W 25 ½" (660) D 19 ¾" (502)
UPS Shippable	Yes

Specifications

Commercial microwave shall have a user-friendly 10 minute dial timer with illuminated digits and an end of cycle audible signal. Timer shall automatically reset if the door is opened during heating with user option to manually reset to zero. There shall be a four power level and cooking stage. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 90°+ opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Interior ceramic shelf shall be sealed and recessed on oven bottom to reduce plate-to-shelf edge impact. Oven shall have a stainless steel exterior and interior and be stackable to save counter and shelf space. The air filter shall be permanently affixed to the front of the oven. Microwave oven shall comply with standards set by the U.S Department of Health and Human Services, UL923 for safety and NSF4 for sanitation.

Warranty

Warranty Certificate for this product can be found on the ACP, Inc. website at:

Intertek


Intertek

www.acpsolutions.com/warranty

Service

All products are backed by the ACP, Inc. 24/7 ComServ





- * Includes handle
- ** IEC 60705 Tested

